

Technical specification sheet

PTR40 | Telescopic Ram

Specifications		
article number		159.000.185
model		PTR40
short description		Telescopic Ram
max. working pressure	psi	7832
battery included		no
spreading stroke 1st plunger	in	8.5
spreading stroke 2nd plunger	in	7.6
total spreading stroke	in	16
retracted length	in	15.2
extended length	in	31.2
max. spreading force 1st plunger	lbf	30574
max. spreading force 2nd plunger	lbf	14613
protection rate		IP57
sound emission @ 1m/3.25ft	dB(A)	78
sound emission @ 4m/13ft	dB(A)	69
hydraulic oil type		ISO-L HV VG 36
number of plungers		2
weight, ready for use	lb	34.2
temperature range	°F	-4 + 131
weight excl. battery	lb	30.9
dimensions (AxBxC)	in	15.2 x 10.1 x 17.4
EN 13204 classification		TR136/215-65/192-15.5
EN 13204 compliant		yes
NFPA 1936, HSF	lbf	30574
NFPA 1936, LSF	lbf	14613
NFPA 1936 compliant		yes

Safety factors / tests	
hydraulic safety factor	2:1
endurance test tool	1000 cycles of spreading while the tool is loaded
endurance test dead man's handle	6000 cycles

Required articles	
Battery PBPA287	151.000.583
Battery Charger PBCH2 (AC-US)	151.000.742
Battery Charger PBCH3 (DC)	151.000.632

